



## WATER LEVEL METER



### FEATURES

- **Ranked #1 by University Field Course**  
Best for accuracy, ease of use and performance
- **Unique Bridge Proof Probe**  
Sets a new standard for probe performance during pump tests and for well sounding
- **Best Resolution & Accuracy**  
1/100 ft or 1mm & 5x more accurate than white tapes.
- **Stainless Steel and Teflon® Probe**  
1/4" standard, 7/16" and 5/8" also available
- **Hook & Cable Protector**  
Protects tape from casing and lets unit hang from casing
- **5 Times More Accurate**  
Than white tapes with complete polyethylene jacket to protect 1/100 ft or 1mm graduations and stranded stainless steel conductors
- **Standard Sensitivity Control**  
Prevents false readings in high conductivity water - ideal for pump and draw down tests

### Field-Tested & Award Winning

Ranked #1 for accuracy, durability and ease of use since 1995. Many of the features found on the original Testwell SST units are also found on these units. This design has been tested extensively in the field for several years now and is a reliable performer. The tapes meet or exceed federal specification US GGG-T-106E (U.S.A.) or EEC CLASS II (Europe) for a guaranteed accuracy of .008%. A flat spring steel core ensures tapes hang perfectly straight in large and small diameter wells. This provides unparalleled accuracy when compared to the flat white tapes, where kinks in the tape introduce slight errors, in addition to the displacement of water changing the static level.

This Testwell Water Level Meter sets new standards for reliability and accuracy. This unit comes standard with a 1/4" stainless steel and Teflon® probe. It uses a shrouded probe and unique probe design to prevent bridging. Bridging is often encountered during pump tests with other units. All units carry a sensitivity adjustment for different water qualities, with a choice of internal or external controls. The time proven Sonalert buzzer is also used on all units.



**Instrumentation  
Northwest, Inc.**

**1-800-776-9355**  
<http://www.inwusa.com>



## WATER LEVEL METER

## SPECIFICATIONS & ORDERING INFORMATION

### Ordering Information

#### MINI REEL E-Z WATER LEVEL METER

##### Polyethylene Tape, 1/4" diameter (6.35mm) probe\*\*

**5A050** 100 foot (30 meter)

**5A055** 150 foot (50 meter)

**5A060** 200 foot (60 meter)

**5A065** 300 foot (100 meter)

**5A070** 400 foot (120 meter)

**5A075** 500 foot (150 meter)

**5A080** 600 foot (175 meter)

\* Other lengths available on request

\*\* 7/16" (11 mm) and 5/8" (16 mm) probes available on request

Information in this document is subject to change without notice

### Specifications

<b>Operating Principle:</b> Water Sensing	Conductivity
<b>Power</b>	9 volt battery
<b>Tape Lengths*</b>	100-600 feet 30-175 meter
<b>Tape Material</b>	Polyethylene
<b>Probe Diameter**</b>	1/4 inch (6.35 mm)
<b>Probe Material</b>	Stainless Steel & Teflon®
<b>Overall Dimensions:</b>	
Width	12 inches
Height	14.5 inches
Depth	9 inches
<b>Shipping Weight</b>	8 pounds

## Instrumentation Northwest, Inc.



#### Sales and Service Locations

8902 122nd Ave NE, Kirkland • Washington 98033 USA  
(425) 822-4434 • (425) 822-8384 FAX • info@inwusa.com

4620 Northgate Boulevard, Suite 170 • Sacramento, California 95834  
(916) 922-2900 • (916) 648-7766 FAX • inwsw@inwusa.com